

| Turntable section                      |                            |
|----------------------------------------|----------------------------|
| DC Motor                               | Motor                      |
| 33 1/3 RPM, 45 RPM RPM                 | Speed                      |
| 0.20%                                  | Wow and Flutter            |
| 67dB or higher (A-weighted, 20kHz LPF) | Signal-to-Noise Ratio      |
| 60dB (unweighted, 20kHz, LPF)          |                            |
| Aluminum Die-cast                      | Platter                    |
| 12", 30cm                              | Diameter of Platter        |
| Tonearm section                        |                            |
| Static Balance, Straight               | Type                       |
| 8.8", 223mm                            | Effective Arm Length       |
| 0 to 5g                                | Stylus Pressure Range      |
| 2.5 to 5.5g                            | Compatible Cartridge Range |
| Supported                              | Anti-skating Adjustment    |
| Cartridge section                      |                            |
| VM-type                                | Type                       |
| Conical                                | Stylus Shape               |
| 20Hz to 20kHz                          | Frequency Response         |
| 24dB at 1kHz, 15dB at 10kHz            | Channel Separation         |
| 1.5dB                                  | Channel Balance            |
| 3.5g±0.5 g                             | Tracking Force             |
| 47k ohms                               | Output Impedance           |
| 3.5mV                                  | Output Voltage             |
| 5.0g±0.3 g                             | Cartridge Weight           |
| 11g (including nuts, screws and wires) | Head-shell Weight          |
| audio-technica ATN3600L                | Stylus Replacement         |
| Analog Output section                  |                            |
| RCA Pin x 1 pair (Chrome-plated)       | Connectors                 |
| Output Voltage                         |                            |
| 4.2mV                                  | PHONO                      |
| 120mV (–13dBV)                         | LINE                       |
| Bluetooth® section                     |                            |
| Approx. 30ft. / 10 meters              | Range                      |
| SBC                                    | Supported Codec            |
| General                                |                            |
| AC 100 to 240V, 50/60Hz                | Power                      |
| < 1.5W (< 0.5W at Standby)             | Power Consumption          |
| 16.5" x 4.6" x 14.0"                   | Overall Dimensions         |
| 420 x 117 x 356 mm                     | (W x H x D)                |
| Approx. 10.8 lbs. 4.9 kg               | Weight                     |

|                                                                                                                                                                                                                                                                               |                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Rubber Sheet, EP Adapter, Counter Weight, Head-shell (MM-type Cartridge audio-technica AT3600L installed), Turntable (Platter), Dust Cover, Rubber Feet fro Dust Cover x2, Hinge x2, RCA Audio Cable, AC Adapter (GPE053A-120050-Z), Owner's Manual (including Warranty Card) | Accessories                                   |
|                                                                                                                                                                                                                                                                               |                                               |
|                                                                                                                                                                                                                                                                               | ※ RoHS complied.                              |
|                                                                                                                                                                                                                                                                               | ※ Specification and design subject to change. |