

Safety Data Sheet

PT1412 Acrylic Transp. Sealer



Safety Data Sheet dated 29/2/2016, version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:
Trade name: Acrylic Transp. Sealer
Trade code: PT1412

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:
Industrial and professional uses (SU3 - SU22)
Varnish for wood

1.3. Details of the supplier of the safety data sheet

Company:
NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1
Competent person responsible for the safety data sheet:
plasticlab@sivam.it

1.4. Emergency telephone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1
Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO2, water spray. Do not use water jet.

Special Provisions: