POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : POLYFAN RUSH

Product code : L0040210

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels

Substance/Mixture

Chemical nature : Dual compound spray filler

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA

Via Cecilio 17 22100 Como- CO-

Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.eu

Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during

office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation. Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 2 H361d: Suspected of damaging the unborn child.

Specific target organ toxicity - single H335: May cause respiratory irritation.

exposure, Category 3, Respiratory

system

Specific target organ toxicity - repeated H372: Causes damage to organs through

exposure, Category 1, hearing organs prolonged or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/ fume/ gas/ mist/

vapours/ spray.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

• 100-42-5 styrene

• 108-31-6 maleic anhydride

Additional Labelling:

EUH208 Contains: cobalt bis(2-ethylhexanoate)May produce an allergic reaction. EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Liquid pigmented dispersion

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]		
styrene	100-42-5 202-851-5 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Note D	>= 20 - < 25		
ethyl acetate	141-78-6 205-500-4 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10		
ethanol	64-17-5 200-578-6 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 10		
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361 Aquatic Chronic 3; H412	>= 0,1 - < 0,25		
cobalt bis(2- ethylhexanoate)	136-52-7 205-250-6 01-2119524678-29	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360Fd Aquatic Acute 1; H400 Aquatic Chronic 3; H412 (Acute M=1)	>= 0,1 - < 0,25		
maleic anhydride	108-31-6 203-571-6 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372	>= 0,001 - < 0,1		
Substances with a workplace exposure limit :					
Talc (Mg3H2(SiO3)4)	14807-96-6 238-877-9		>= 20 - < 30		
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 1 - < 10		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

according to Regulation (EC) No. 830/2015

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

4.1 Description of first aid measures

General advice : When symptoms persist or in all cases of doubt seek medical

advice.

Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Take off all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Do NOT use solvents or thinners. Put shower on working place

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart.

Seek medical advice.

Put eye-washer on working place

Remove contact lenses.

If swallowed : If accidentally swallowed obtain immediate medical attention.

Do NOT induce vomiting.

Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

Seek medical advice.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Keep containers and surroundings cool with water spray.

Unsuitable extinguishing

media

: Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during : As the product contains combustible organic components, fire

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

firefighting will produce dense black smoke containing hazardous

products of combustion (see section 10).

Exposure to decomposition products may be a hazard to

health.

Cool closed containers exposed to fire with water spray.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along

floors.

Ensure adequate ventilation.
Use personal protective equipment.

Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.

Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area

should be cleaned up immediately with a suitable

decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol

(50 parts)/concentrated

(d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.

Clean contaminated surface thoroughly.

Dam up.

Soak up with inert absorbent material and dispose of as

hazardous waste.

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid exceeding the given occupational exposure limits (see

section 8).

Use only in area provided with appropriate exhaust ventilation.

Avoid contact with skin, eyes and clothing.

Smoking, eating and drinking should be prohibited in the

application area.

Avoid inhalation of vapour or mist. For personal protection see section 8.

Thoroughly mix before using

After using, store in a well-sealed container

Advice on protection against

fire and explosion

: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than

the occupational exposure limits.

When transferring from one container to another apply earthing measures and use conductive hose material.

No sparking tools should be used.

The product should only be used in areas from which all naked lights and other sources of ignition have been

excluded. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Observe label precautions.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Solvent vapours are heavier than air and may spread along

floors.

Vapours may form explosive mixtures with air.

Electrical installations / working materials must comply with

the technological safety standards.

Keep away from sources of ignition - No smoking.

Store between 5° an 35°C in a dry, well ventilated place away

from source of heat, ignition and direct sunlight.

Store in accordance with the particular national regulations.

Advice on common storage

: Keep away from oxidizing agents and strongly acid or alkaline

materials.

: 3 Flammable liquids German storage class

7.3 Specific end use(s)

: This information is not available.

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

SECTION 8: Exposure controls/personal protection

8.1 Components with workplace control parameters

Components	CAS-No.	Value type	Control parameters	Update	Basis
		(Form of	/ Permissible		
		exposure)	concentration		
styrene	100-42-5	TWA	10 ppm	2020	ACGIH
		STEL	20 ppm	2020	ACGIH
Talc (Mg3H2(SiO3)4)	14807-96-6	TWA	0,1 mg/m3	2017-12-27	2004/37/EC
		(Respirable			
		dust)			
Further information: Carcinogens or mutagens					
titanium dioxide	13463-67-7	TWA	10 mg/m3	2014-03-01	ACGIH
			(Titanium dioxide)		
ethyl acetate	141-78-6	STEL	400 ppm	2017-02-01	2017/164/EU
-			1.468 mg/m3		
Further information: Indicative					
		TWA	200 ppm	2017-02-01	2017/164/EU
			734 mg/m3		
Further information: Indicative					
ethanol	64-17-5	TWA	1.000 ppm	2013-03-01	ACGIH
maleic anhydride	108-31-6	TWA	0,01 mg/m3	2016-03-01	ACGIH

DNEL styrene

: End Use: Workers

Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 406 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 85 mg/m3

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects

Value: 289 mg/m3

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute local effects

Value: 306 mg/m3

End Use: Consumers Exposure routes: Oral

Potential health effects: Long-term systemic effects

Value: 2,1 mg/kg

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

End Use: Consumers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 343 mg/kg

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 10 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Acute systemic effects

Value: 174,25 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Acute local effects

Value: 182,75 mg/m3

1-isopropyl-2,2dimethyltrimethylene diisobutyrate : End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 5 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 17,62 mg/m3

End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 5 mg/kg

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 4,35 mg/m3

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 5 mg/kg

cobalt bis(2-ethylhexanoate)

: End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 235,1 μg/m³

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 37 μg/m³

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

End Use: Consumers Exposure routes: Oral

Potential health effects: Long-term systemic effects

Value: 55,8 μg/kg bw/day

titanium dioxide : End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 10 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 10 mg/m3

End Use: Consumers Exposure routes: Oral

Potential health effects: Long-term systemic effects

Value: 700 mg/kg

PNEC

styrene : Fresh water

Value: 0,028 mg/l

Marine water Value: 0,014 mg/l

Fresh water sediment Value: 0,614 mg/kg

Marine sediment Value: 0,307 mg/kg

Soil

Value: 0,2 mg/kg

Sewage treatment plant

Value: 5 mg/l

1-isopropyl-2,2-dimethyltrimethylene

diisobutyrate

: Fresh water

Value: 0,014 mg/l

Marine water Value: 0,0014 mg/l

Fresh water sediment Value: 3 mg/l

varac. 5 m

Soil

Value: 0,926 mg/kg

cobalt bis(2-ethylhexanoate) : Fresh water

Value: 3 µg/l

9 / 18

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Marine water Value: 2,36 μg/l

Sewage treatment plant Value: 0,37 mg/l

Fresh water sediment Value: 9,5 mg/kg

Marine sediment Value: 9,5 mg/kg

Soil

Value: 10,9 mg/kg

titanium dioxide : Marine water

Value: 0,0184 mg/l

Fresh water Value: 0,184 mg/l

Intermittent use/release Value: 0,193 mg/l

Sewage treatment plant

Value: 100 mg/l

Marine sediment Value: 100 mg/kg

Fresh water sediment Value: 1000 mg/kg

Soil

Value: 100 mg/kg

8.2 Exposure controls

Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational

exposure limits.

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in

exceptional cases suitable respiratory equipment should be

worn only for a short period of time.

Respirator with combination filter for vapour/particulate (EN

141)

Hand protection : Solvent-resistant gloves (butyl-rubber)

For prolonged or repeated contact use protective gloves.

Protective gloves complying with EN 374.

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of

the CE approved gloves.

Barrier creams may help to protect the exposed areas of skin,

they should however not be applied once exposure has

occurred.

Skin should be washed after contact.

Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.

Personnel should wear protective clothing. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Odour : solvent-like

Flash point : $0 - < 21 \,^{\circ}\text{C}$

Ignition temperature : not determined

Lower explosion limit : No data available

Upper explosion limit : No data available

Auto-ignition temperature : Not applicable

pH : not determined

Freezing point : Not applicable

Boiling point : not determined

Vapour pressure : 1,000 hPa

at 50 °C

according to Regulation (EC) No. 830/2015

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Density : 1,4972 g/cm3

Water solubility : not determined

Partition coefficient: n-

octanol/water

: No data available

Solubility in other solvents : not determined

Flow time : 20 s

8 mm

Method: DIN 53211

Relative vapour density : Not applicable

Evaporation rate : not determined

9.2 Other information

Solids by weight : 73,53 %

Volatile organic compounds :

(VOC) content

26,46 %

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety

standards to avoid decomposition and degrading under the

defined conditions.

Taking the product type into account, it is advisable to leave

the product in its original packaging thus avoiding transferring $\ddot{}_{\cdot\cdot}$

It.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

according to Regulation (EC) No. 830/2015

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Thermal decomposition : Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation

method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause

removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind

in assessing the toxicological effects deriving from the

preparation.

Components:

styrene:

Acute oral toxicity : LD50: 5.000 mg/kg, Rat Acute inhalation toxicity : LC50: 11,8 mg/l, 4 h, Rat,

Acute dermal toxicity : LD50: > 2.000 mg/kg, Rat, OECD Test Guideline 402

maleic anhydride:

Acute inhalation toxicity : LC50: > 4,35 mg/l, 4 h, Rat,

Talc (Mg3H2(SiO3)4):

Acute oral toxicity : LD50: > 5.000 mg/kg

SECTION 12: Ecological information

12.1 Toxicity

cobalt bis(2-ethylhexanoate) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

styrene : NOEC: 1,01 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

12.2 Persistence and degradability

Biodegradability : No data available

according to Regulation (EC) No. 830/2015

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological

information

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Disposal together with normal waste is not allowed. Special

disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 Proper shipping name

ADR PAINT RELATED MATERIAL

IMDG PAINT RELATED MATERIAL

IATA PAINT RELATED MATERIAL

according to Regulation (EC) No. 830/2015

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

Special Provisions : Special Provision 640D

IMDG

Packing group : II
Labels : 3

EmS Code : F-E,S-E

IATA

Packing group : II
Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation

: Not applicable

REACH - List of substances

subject to authorisation

(Annex XIV)

(Article 59).

: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles

(Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. preparations and articles (Annex XVII)

: Banned and/or restricted

67-56-1 methanol

Regulation (EC) No 649/2012 : Not applicable of the European Parliament and the Council concerning the export and import of dangerous chemicals

MAL-Code-Number : 4-6 (1993)

3.164-m3 air/10 g

PR-Number (DK) : 4380531

Storage class (TRGS 510) : 3: Flammable liquids

Risk classification according

to VbF

: Flash point less than 21 °C, at 15 °C not miscible in water

Specially dangerous flammable liquids

Water contaminating class

(Germany)

: highly hazardous to water

Ordinance on facilities for handling substances that are

hazardous to water (AwSV)

16 / 18

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

Classification according to AwSV, Annex 1 (5.2)

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

List of references

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended). Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Key or legend to abbreviations and acronyms used in the safety data sheet

POLYFAN RUSH

Version 1.30 Revision Date 22.12.2021 Print Date 23.12.2021

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO -International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.